


Product


KFO 5432



KFO-5432 is a crimping tool for fiber optic connectors, 3.25 mm, 3.84 mm, 5.41 mm, 5.00 mm, 4.52 mm/.128", .151", .213", .197", .178", HEX-Crimp. ST, SC, SMA, SMB, SFR.



Die profile



Crimp profile

- High strength, through hardened alloy steel construction
- Unique mechanism significantly reduces hand force requirement over competing crimping tools
- Versatile and easy to customize for right hand or left hand users.
- Non-slip pad holds tool in place when leveraging on a work surface
- Full cycle crimp mechanism to ensure consistent, reliable crimp
- Ratchet release mechanism to clear miscrimps and obstructions
- Precision eccentric adjustment for consistent performance and ability to calibrate
- Hole in handle allows attachment of safety strap
- Each tool has a unique serial number for traceability

TECHNICAL DATA

Length: 256 mm/10.08"

Width: 22 mm/0.87"

Height: 80 mm/3.15"

Weight: 565 gr/1.25 lb

Crimp dimensions mm/mm²:
3,25 mm/3,84 mm/5,41 mm/5,00 mm/4,52 mm

Crimp dimensions inch/AWG:
.128"/.151"/.213"/.197"/.178"

Connector: Fiber optic

Description: For example SMA, SMB, SFR, ST, SC.

Life span, cycles: 50,000