


Product

# KRB 0115S



KRB-0115S is a crimping tool for non insulated open barrel connectors, 2.8 + 4.8 mm, 0.1 - 1.5 mm<sup>2</sup>/.110" + .187", AWG 26-16, B/F-Crimp.

- High strength, through hardened alloy steel construction
- Unique mechanism significantly reduces hand force requirement over competing crimping tools
- Versatile and easy to customize for right hand or left hand users.
- Non-slip pad holds tool in place when leveraging on a work surface
- Full cycle crimp mechanism to ensure consistent, reliable crimp
- Ratchet release mechanism to clear miscrimps and obstructions
- Precision eccentric adjustment for consistent performance and ability to calibrate
- Hole in handle allows attachment of safety strap
- Each tool has a unique serial number for traceability



Die profile



Crimp profile

#### TECHNICAL DATA

**Length:** 204 mm/8.03"

**Width:** 22 mm/0.87"

**Height:** 76 mm/2.99"

**Weight:** 560 gr/1.23 lb

**Wire size:** 0.1-1.5 mm<sup>2</sup> / AWG 26-16

**Crimp dimensions mm/mm<sup>2</sup>:**

0,1 - 0,5 mm<sup>2</sup>/0,5 - 1 mm<sup>2</sup>/0,5 - 1,5 mm<sup>2</sup>

**Crimp dimensions inch/AWG:**

AWG 26 - 20/AWG 20 - 18/AWG 20 - 16

**Connector:** Uninsulated open barrel connectors

**Description:** For uninsulated open barrel connectors.

**Life span, cycles:** 50,000