


Product **KRB 0560**



KRB-0560 is a crimping tool for non insulated connectors 6.3 mm, 0.5 - 6 mm²/.250", AWG 22-10, B/F-Crimp. Short and long handle available.

- · High strength, through hardened alloy steel construction
- Unique mechanism significantly reduces hand force requirement over competing crimping tools
- · Versatile and easy to customize for right hand or left hand users.
- · Non-slip pad holds tool in place when leveraging on a work surface
- · Full cycle crimp mechanism to ensure consistent, reliable crimp
- · Ratchet release mechanism to clear miscrimps and obstructions
- · Precision eccentric adjustment for consistent performance and ability to calibrate
- · Hole in handle allows attachment of safety strap
- · Each tool has a unique serial number for traceability





Crimp profile

TECHNICAL DATA

Length: 256 mm/10.08" Width: 22 mm/0.87" Height: 80 mm/3.15" Weight: 560 gr/1.23 lb Wire size: 0.5-6 mm² / AWG 22-AWG 10 Crimp dimensions mm/mm²: 0,5 - 1,5 mm²/1,5 - 2,5 mm²/4 - 6 mm

Crimp dimensions inch/AWG:

AWG 22 - AWG 16/AWG 16 - AWG 14/AWG 12 - AWG 10 Connector: Uninsulated open barrel connectors Description: For uninsulated open barrel connectors.

Life span, cycles: 50,000

Pressmaster AB P.O. Box 3, Industrivägen SE-796 21 Älvdalen, Sweden Tel: +46 (0)251-451 00 info@pressmaster.se www.pressmaster.com