


## Product

## KRS 1560L-4



KRS-1560L-4 is a crimping tool for Solar connectors like MC4<sup>™</sup> and similar connectors, Ø 4 mm/.157", with openbarrel conductor crimp 1.5 - 2.5, 4.0, 6.0 mm²/AWG 16 - 14, 12, 10. This tool also exist in versions for MC3<sup>™</sup> and SOLARLOK<sup>™</sup> connectors. (MC3<sup>™</sup> and MC4<sup>™</sup> are trademarks owned by Multi-Holding AG, Switzerland. SOLARLOK<sup>™</sup> is a trademark owned by TE Connectivity, USA)



- Unique mechanism significantly reduces hand force requirement over competing crimping tools
- Versatile and easy to customize for right hand or left hand users.
- Non-slip pad holds tool in place when leveraging on a work surface
- Full cycle crimp mechanism to ensure consistent, reliable crimp
- Ratchet release mechanism to clear miscrimps and obstructions
- Precision eccentric adjustment for consistent performance and ability to calibrate
- Hole in handle allows attachment of safety strap
- Each tool has a unique serial number for traceability





Die profile

Crimp profile

TECHNICAL DATA
Length: 256 mm/10.08"
Width: 22 mm/0.87"
Height: 80 mm/3.15"
Weight: 642 gr/1.42 lb

Wire size: 1.5-6 mm<sup>2</sup> / AWG 16-

AWG 10

Crimp dimensions mm/mm<sup>2</sup>: 1,5 - 2,5 mm<sup>2</sup>/4 mm<sup>2</sup>/6 mm<sup>2</sup> Crimp dimensions inch/AWG: AWG 16 - 14/AWG 12/AWG 10 Connector: Uninsulated open barrel

connectors

**Description:** For Solar connectors like MC4 $^{\text{TM}}$  and similar connectors,  $\emptyset$ 

4 mm/.157 inch

Life span, cycles: 50,000