


## RRB 0315L



RRB-0315L is a crimping tool for Super Seal type connectors with seal, uninsulated open barrel connectors, 0.35 - 1.5 mm<sup>2</sup>/AWG 22-16, B/F-Crimp.

- Unique "snap on" locator design for full visibility of connector and wire insertion
- Parallel action for precision and consistent crimp results
- Full cycle crimp mechanism to ensure consistent, reliable crimp
- Ratchet release mechanism to clear miscrimps and obstructions
- Precision eccentric adjustment for consistent performance and ability to calibrate
- Tool-less die closure adjustment for maintenance and calibration
- · Small size makes it easy to use in confined areas
- · Hole in handle allows attachment of safety strap
- · Each tool has a unique serial number for traceability





Crimp profile

TECHNICAL DATA Length: 230 mm/9.06" Width: 22 mm/0.87" Height: 75 mm/2.95" Weight: 443 gr/0.98 lb Wire size: 0.35-1.5 mm<sup>2</sup> / AWG 22-AWG 16 Crimp dimensions mm/mm<sup>2</sup>: 0,35 - 0,5/0,75 - 1,5 Crimp dimensions inch/AWG: AWG 22 - AWG 20/AWG 20 - AWG 16 Connector: Connectors with seal, 1.5 system type. Description: For non insulated open barrel super seal connectors Life span, cycles: 50,000

Pressmaster AB P.O. Box 3, Industrivägen SE-796 21 Älvdalen, Sweden Tel: +46 (0)251-451 00 info@pressmaster.se www.pressmaster.com